

## Technical Data

### Performance Data - RGM

Model M³/H		6"	8"	10"	12"	14"	16"
50	Vel	1.59	0.89				
	Pt.	22	5				
100	Vel	3.14	1.80	1.15	0.8		
	Pt.	55	27	8	3		
150	Vel	4.75	2.65	1.70	1.20	0.90	0.70
	Pt.	120	43	26	8	5	2
200	Vel	6.30	3.55	2.30	1.60	1.15	0.90
	Pt.	200	75	33	25	8	5
250	Vel	7.90	4.40	2.85	2.00	1.45	1.10
	Pt.	250	105	46	31	20	8
300	Vel	9.45	5.32	3.40	2.40	1.75	1.35
	Pt.	300	150	70	69	26	20
400	Vel		7.9	4.55	3.19	2.30	1.75
	Pt.		250	110	55	33	27
500	Vel		8.85	5.68	3.98	2.90	2.20
	Pt.		279	172	90	46	33
600	Vel			6.8	4.75	3.45	2.65
	Pt.			220	115	71	42
700	Vel			7.95	5.55	4.10	3.10
	Pt.			260	165	90	52
800	Vel			9.10	6.36	4.65	3.55
	Pt.			286	200	115	75
900	Vel				7.15	5.20	3.95
	Pt.				220	150	90